

# Little Greene®

— PAINT & PAPER —

## Intelligent ASP

### Description:

A high opacity, low odour water-based matte primer/undercoat. Suitable for painting on most interior and exterior surfaces with excellent adhesion to existing aged alkyd finish.

### Properties:

<b>Gloss Level</b>	<b>Theoretical coverage</b>	<b>Recommended film thickness</b>	<b>Recommended number of coats</b>	<b>Surface dry</b>	<b>Time to recoat*</b>
Matte (<6%)	529ft <sup>2</sup> per gallon (varies with surface porosity & texture)	30 microns dry, per coat.	1 or 2 as required	1 hour*	4 hours minimum*
<b>Volume solids</b>	<b>Colour Availability</b>	<b>Available pack sizes</b>	*Complete cure (drying) of the coating can take up to several days, depending on the film thickness applied and the ambient drying conditions at site. The coating should not be exposed to heavy surface condensation, as can be found in kitchens and bathrooms, before it is completely dry as this can cause permanent surface marking.		
38%	All Little Greene colour ranges	Quart & 1 Gallon			

### Approvals & Standards:

#### Quality Control:

Manufactured under the auspices of I ASQ/ ANSI/ SO 9001:2015 quality & ASQ/ANSI/ ISO 14001:2015 environmental management systems.

#### Child Friendly:

ASTM F963:2017/BS EN71 -3:2019 Safety of toys. Specification for migration of certain elements. (Test certificate available upon request)

#### VOC Content:

SCAQMD Rule 1113 <50g\* g/l.  
\*South Coast Air Quality Management District

Lead V4.1 (VOC Content).

#### Wash/Scrub Resistance:

This product has been tested under the regulations DIN EN 13 300 and has been classified;  
Wet scrub resistance – Class 2. Gloss – Dead Matt.  
Contrast Ratio – Class 1. Largest Grain Size – Fine.  
Theoretical Spreading Rate – 529ft<sup>2</sup> per gallon.

### Surface Preparation:

**New wood:** For soft woods, knots should be sealed with knotting compound to prevent staining and then primed with Little Greene Intelligent ASP. Resinous hard woods require cleaning and treatment with a suitable primer (consult the relevant product data sheets for further details) prior to undercoating. Ensure moisture content of the timber is below 15% before commencing application. Damp wood should never be painted as this may give rise to blistering, flaking, cracking and premature coating failure. Green oak should not be painted unless it has been weathered for at least 6 months.

**Metals:** New ferrous/non-ferrous metalwork should be hand or mechanically cleaned, to remove any surface rust before application. Bare or corroded Iron or Steel will require treating with at least 2 coats of Little Greene Intelligent ASP.

**Existing paint finish:** Remove all loose and flaking paintwork. Degrease with a suitable detergent solution, such as sugar soap, followed by clean water rinse. Rub down thoroughly with a medium grade sandpaper to provide a key and a defect free smooth surface, "feathering in" areas where paint has been removed. Make good any repairs, sand and apply primer to exposed surface as appropriate. **WARNING!** If you scrape sand or remove old paint, you may release lead dust. LEAD is toxic, exposure to LEAD DUST can cause serious illness such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Plastics:** For long term performance, clean & abrade all surfaces thoroughly to provide a key before application.

**New plaster walls:** For plaster skim, allow at least four weeks for the plaster to thoroughly dry. Apply a primer coat by thinning the paint with a 5% to 25% (v/v) addition of clean water, depending upon the porosity of the substrate. Cut in by brushing at the same dilution recommendation as for priming, to promote flow and sealing of the substrate. For new, fully plastered walls, allow at least six months for the plaster to thoroughly dry before painting with Little Greene Intelligent ASP. This product is not recommended for painting lime or other natural plasters.

**Existing plaster walls:** Lightly wash any existing paint work to remove any dust or surface laitance. Apply a primer coat by thinning with a 5% to 10% (v/v) addition of clean water, depending upon the porosity of the substrate. Finish by applying at least one/two full coats, as required. This product is not recommended for painting previously painted lime or other natural plaster.

# Little Greene®

— PAINT & PAPER —

## Intelligent ASP

### Application:

Stir thoroughly before use. Do not apply to surfaces when the ambient temperature is below 5°C/41°F or if there is a risk of rain during application or drying. To obtain a good flow apply generously avoiding runs and sags.

**Brushing:** Use a high quality synthetic bristle brush that is suitably sized for the project at hand. New brushes should be conditioned by washing in clean water and thoroughly dried with a clean, lint free, cloth.

Avoid immersing brush too far into the paint to prevent paint from entering the ferrule. Avoid drips and splashes by not overloading the brush. Apply paint in even strokes and only extend painting area such that a wet edge can be easily maintained. For the highest quality appearance, keep final brush strokes all in the same direction and never go over paint that has already begun to dry.

For intricate items, or where high ambient temperatures/high air flow conditions cannot be avoided, the open time may be extended with a 10% to 15% (v/v) addition of clean water. This advice is also applicable to large flat areas; however, use of a paint roller is the recommended application method in such cases.

Lightly rubbing down between coats will remove any dust motes and other surface contamination, producing a near professional finish other surface contamination, producing a near professional finish.

**Roller:** Use a short nap wool blend type sleeve for best appearance on smooth surfaces. Increase nap length for textured surfaces, as appropriate, to ensure even and thorough coverage. Keep final strokes all in the same direction, maintaining a wet edge throughout. Never be tempted to go over already drying paint as this will lead to lap marking and flashing. When high ambient temperatures/high air flow conditions cannot be avoided, the open time may be extended with a 10 to 15% (v/v) addition of propriety water-based paint.

### Spray Finishing Guidelines:

#### Conventional:

Thin with up to	40%(v/v) water
Tip size:	1.60 to 2.00 mm (62 to 78 thou)
Air pressure:	0.28 to 0.41 MPa (40 to 60 psi)

#### Airless

Thin with up to	20%(v/v) water
Tip size:	0.28 to 0.54 mm (11 to 21 thou)
Pressure at tip:	12.6 to 19.6 MPa (1800 to 2800 psi)

### Cleaning:

Remove excess paint and clean all equipment using clean water immediately after use. Never store brushes or roller sleeves in water as this will result in deterioration of their application performance.

### Storage & Shelf Life:

Store unused paint in a cool, dry, frost free area away from direct sunlight. Ensure tin lids are securely and correctly replaced after use.

When unopened and stored under the conditions above, this product is stable for a minimum period of two years.

### Aftercare:

**Cleaning:** For light surface soiling; use a dilute, lukewarm solution of domestic washing up liquid and a clean sponge or lint free cloth. Ensure sponge or cloth is wet (but not dripping), wash the affected area and repeat as required.

Ensure radiators are at room temperature before attempting to clean using the procedure above. Cleaning hot radiators may result in localised or uneven polishing of the surface.

To help prevent general build up of contamination on paint surface, keep your home well-ventilated during activities likely to contribute to oil and grease accumulation, like cooking. Tackle dust generated from DIY by, preferably, collecting at source or thorough vacuum cleaning.

To prevent marking, always use a soft brush attachment to vacuum clean adjacent surfaces.

**Special Care:** Avoid placing heavy objects onto the surface for a least a week after painting. Bookshelves and other frequent use surfaces may benefit from a very light application of beeswax polish to help prevent marring over the long term.

**Repair:** Lightly rub down area to be repainted, apply suitable primer to any exposed substrate. Repaint the whole item/area with one or two coats as required. Spot repairs will almost always result in an inferior aesthetic appearance.

### Disposal & Recycling

Dispose of excess or waste paint via a licensed waste handing operator. Empty metal containers may be recycled (remove wire handle on gallon can).

### Health & Safety

Always read the label on the can before use. Ensure maximum ventilation during application and drying. Consult product material safety data sheet for further details. In case of eye contact, flush immediately with water for at least 15 minutes. On skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention.

If you have trouble breathing, leave the immediate area to obtain fresh air. If continued difficulty in breathing is experienced seek immediate medical attention. Keep out of reach of children. Refer to the Safety Data Sheet for further information.

**Disclaimer** - The information on this data sheet is correct to the best of our knowledge and experience. The Little Greene Paint Company reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, not does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.

Little Greene Corporation, 9 East Putnam Avenue, Greenwich, CT. 06830.

Customer Service: [getintouch@littlegreene.us](mailto:getintouch@littlegreene.us) | [www.littlegreene.us](http://www.littlegreene.us) | Tel: 1-888-516-6130